



Color: ■ orange Similar to illustration

Technical data	
Marking method	Thermal transfer
Marking	1, , 2, , 3, , 4, , 5, ; to 46, , 47, , 48, , 49, , 50, ;
Marking (number)	1
Marking direction	Horizontal marking
Marking color	black
Marking type	Numbers
Marking differentiation	Consecutive numbers per strip
Delivery form	Marker card
Delivery form configuration	10 strips with 10 markers per card
Flammability class per UL94	V0

Physical data	
Marker/strip width	5 mm
Marker width	5 mm

Mechanical data	
Smear resistance	EN 60998-1:2004

Material data	
Color	orange
UV resistance	EN 60068-2-5:2010 Procedure B
Halogen-free	Yes
Weight	6.7 g
Fire load	0.201 MJ



Commercial data		
Product Group	9 (Std Chassis Mt Blocks)	
eCl@ss 10.0	27-14-11-37	
eCl@ss 9.0	27-14-11-37	
ETIM 8.0	EC000761	
ETIM 7.0	EC000761	
PU (SPU)	50 (5) pcs	
Packaging type	Box	
Country of origin	DE	
GTIN	4017332388542	
Customs tariff number	49119900000	

Environmental Product Compliance		
RoHS Compliance Status	Compliant,No Exemption	

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance
264-900/000-012

↓

Installation Notes

Marking



Marking via Mini-WSB Quick Marking System.