

EKDS16124-316

Stainless steel compact version, double door enclosure



The stainless steel double door compact floor standing enclosure range, EKDS, with a IP 55 protection degree is ideal for installation in confined spaces where a single door when opened, would take up too much space in front of the enclosure. The doors' loading capacity also increases as it is divided over two doors. With an IP 55 protection degree, components inside the enclosure are well protected and makes the it well suited for almost any environment, grade dependant. IP 66 protection degree variant as individual doors with vertical middle divider also available.



IP 55 | TYPE 12 | IK 10; IP 66 | TYPE 4X (on request)

IP 55 | TYPE 12 | IK 10

H	1600
W	1200
D	400
w	1094
h	1494
Weight (kg)	148.00
Item no.	EKDS16124-316

Material: AISI 304L pre-grained stainless steel / AISI 316L.
Body and removable rear panel: 1.5 mm. Door: 2 mm. Bottom
Plates: 1.5 mm. Mounting plate: 3 mm galvanized steel.

Body: One piece enclosure body. Integrated depth profiles with
hole pattern allowing mounting plate adjustable in depth.

Door: Surface mounted with 4 hinges including door frame with 25 mm
hole pattern and earthing studs. Standard doors can not be reversed.

Rear panel: Fitted by M6 torx screws. Standard facilities for rear
door mounting. Split rear panels in 1600 mm wide enclosures.

Lock: Espagnolette 4-point locking system in the main door
and 2-point locking system in the slave door. Standard double-
bit lock with 3 mm insert. Standard inserts, cylinders, lift
handles and T-handles are available as accessories.

Bottom plates: One piece bottom plate with injected
polyurethane gasket to ensure maximum sealing.

Earthing: Door is equipped with separate welded earthing studs
and earthing to the frame can be accomplished by using the ECF.

Mounting plate: Double folded and slides into position. Adjustable
in depth by steps of 25 mm. Mounting plate is supplied, attached
on the outside of the enclosure packaging. Fitted inside for 1600
mm wide enclosures. For 1600 mm wide, filler plate is included.

Finish: 400 pre-grained stainless steel.

Protection: Double door version, complies with IP 55 |
TYPE 12 | IK 10. Individual doors with welded vertical
divider, complies with IP 66 | TYPE 4X, 12 | IK 10.

Delivery: One piece body with fitted door and rear panel, bottom
plates and mounting plate, including door earthing studs. Delivered
on a pallet which is identical to the width of the enclosure to allow
suiting without removal. Mounting plate is attached to the outside
of the enclosure packaging. All the packing material is recyclable.