



Description: Lighting system with a compact design, suitable for all types of enclosures or racks. It has three possible fixing possibilities: magnetically, screw mounting with a variable distance between holes and/or snap-into 19" rack. This lamp has a very long service life (around 50000 h.) due to the use of LED technology. The body of the lighting system is made of PC-ABS. An integrated connector allows the activation of the lamp by a door switch by using the TLCS product without performing any additional wiring. The led-tube is made of PC and the colour of the light is white.

Lamp type: High Power LEDs.

Luminosity: 945 Lm.

Power consumption: 7.2 W.

Operating temperature: -20 °C to +50 °C.

Dimensions: 448 x 54.5 x 26 mm.

Connections: 2x0.75 mm² open end cable (1.5 m long),
2x0.75 mm² mini-connector for door switch use.

Approvals: CE, EAC.

Delivery: 1 light with fix mounted connection cable, integrated magnets and mounting screws.

Operating voltage	Finish	CatalogNumber
220-240 V AC, 50/60 Hz	Light grey (RAL 7035)	TLCL87035
24 V DC	Light grey (RAL 7035)	TLCL87035-24
220-240 V AC, 50/60 Hz	Black (RAL 9005)	TLCL89005
24 V DC	Black (RAL 9005)	TLCL89005-24

100-240 V version available on request.