

DEUR, VEILIGHEIDSGLAS, 500X400, PLAATSTAAL, BINNENWERK DUBBELE BAARD 3 MM

CATALOGUSNUMMER

ADC05040R5



De elektrische componenten kunnen worden bekeken terwijl de deur gesloten is. Deze zorgt ervoor dat onbevoegde personen geen toegang hebben en dat de bescherming tegen binnendringing van stof en vocht wordt gehandhaafd.

KENMERKEN

Omschrijving: Ter vervanging van de standaard deur, geeft goed zicht op de gemonteerde apparatuur in de kast. Alle opties uit het slotenprogramma zijn mogelijk.

Materiaal: 1.2 mm plaatstaal / 1.5 mm voor behuizingen met een hoogte of breedte van 500 mm of meer / 2 mm voor behuizingen met een hoogte of breedte van 800 mm of meer. Voorzien van 4 mm veiligheidsglas.

Afwerking: Structuur poedercoating, RAL 7035.

Beschermingsklasse: Overeenkomstig IP 55 | TYPE 12, 13, IK 07.

Verpakkingseenheid: 1 deur.

PRODUCTKENMERKEN

Article Number: ADC05040R5

Hoogte: 495 mm

Breedte: 395 mm

Diepte: 15 mm

Materiaal: Plaatstaal

Latch Quantity: 1

Afwerking: Structuur poedercoating

Kleur: Lichtgrijs

Color Code: RAL 7035

Dikte: 1.5 mm

Package Quantity: 1

Gewicht: 4.3 kg

ADDITIONAL PRODUCT DETAILS

3-punts espagnolette slotsysteem. Niet geschikt voor AFS.



nVent.com

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF

TRACER

© 2024 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.