

SPECTRA BINNEN-SS,1000W,115V, SPECTRACOOOL G28, 4X UITVOERING, SS, 1 FASE 50/60HZ

CATALOGUSNUMMER

G280416G051



SpectraCool Air Conditioners are available in three sizes that offer a broad range of cooling capacities and configurations. These units deliver reliable enclosure cooling in demanding environments that features reliable design, clean appearance, easy installation, and a filterless design.

Select units come with Remote Access Control (RAC), an integrated, parametric controller designed to work seamlessly with our enclosure air conditioner units for the purpose of remotely monitoring and managing anywhere from a single unit to an entire network of Spectra cool air conditioners from virtually anywhere in the world with a secure internet connection. Ensure that your systems are always running at optimal temperature levels, increase productivity and improve overall system reliability.

KENMERKEN

Attractive industrial design with minimal use of visible fasteners

Energy-efficient rotary compressor on most models

Cleanable, reusable aluminum mesh filter included to protect coils for maximum cooling performance in dirty environments

R407c and R134a refrigerants

115, 230 and 400/460 VAC 3-phase power input on most models

Reliable mechanical thermostat on enclosure side of the unit

All G-series come standard with two separate thermostats for cooling and heating when a heater is equipped

Dust-resistant condenser coil allows the unit to be run filterless in most indoor applications

Dual condenser-side air movers for performance redundancy on G52 and G57 models

Galvanized or stainless steel cover for rugged factory and outdoor environments

Exterior and partially recessed mounting options

Easy-mount flanges for simple installation

Every unit functionally tested before shipping

Les modèles standard de climatiseur intérieur comprennent également : Gestion active des condensations avec bande chauffante, relais d'arrêt pour commutateur de porte et autres exigences du système, interrupteur de défectuosité et affichage numérique côté ambiant

Standard Outdoor Air Conditioner models also include: Telcordia GR-487 capable*, Corrosion-resistant coatings on condenser coil for Type 4 units and on condenser coil and ambient-side copper joints for 4X units, malfunction switch, compressor heater, head pressure control, standard G28/G52 units have 2000W, and operating temperature range from -40 F/-40 C to 131 F/55 C

Remote Access Control Units support up to 2 temperature sensors and 10 alarms. They support multiple communication protocols: SNMP, Modbus TCP, Ethernet/IP, and Profinet.

Mounting hardware, gaskets and user manual furnished with the unit

PRODUCTKENMERKEN

Article Number: 20932

Hoogte: 726 mm

Breedte: 432 mm

Diepte: 284 mm

Nominale spanning: 115 V

Remote Access Control: No

Nominal Capacity Btu/h: 4900 Btu/h

Nominal Capacity Watts: 1172 W

Bedrijfstemperatuur: 10 – 55 °C

Max Current: 11.4 A

Materiaal: Stainless Steel 304

Afwerking: Brushed #3

Kleur: Unpainted

Dikte: 1 mm

ADDITIONAL PRODUCT DETAILS

*Partial Recess Mount units are not eligible for Type 4 or 4X ratings. Also not eligible for Telcordia GR-487 certification.

Cutout Adapter options for enclosures with older nVent HOFFMAN or Competitive units for easy transitions to new air conditioners



nVent.com

TRACER

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF