


DIEPTESCHEIDINGSPROFIEL, 500

CATALOGUSNUMMER

VBD500



Het dieptescheidingsprofiel vergroot de beschikbare montagemogelijkheden binnen de behuizing, en verdeelt deze in twee bruikbare ruimtes.

KENMERKEN

Omschrijving: Gemonteerd in het midden van een 1200 mm of 1600 mm brede behuizing (boven- en onderzijde) om standaard montageopties mogelijk te maken in twee secties van 600 mm of 800 mm breed. Dit maakt het mogelijk accessoires separaat te monteren zoals CAB(P), CBU, CLPK, CLPF etc., in iedere kant van de behuizing. Accessoires zijn verstelbaar in diepte binnen het 25 mm gatenpatroon.

Materiaal: 1.75 mm verzinkt plaatstaal.

Verpakkingseenheid: 2 stuks, zonder bevestigingsmateriaal.

Montagevoorschriften: Voeg VBK toe voor montage. Voeg VB toe voor volledige montageopties bij de scheiding.

Add VBK for mounting. Add VB for complete mounting facilities in the division

The dividing bar replicates the enclosure's frame vertically both in the front and rear, increasing the mounting possibilities available

The bar divides the enclosure into two internally useable spaces, where more accessories can be mounted, providing a cost effective solution

PRODUCTKENMERKEN

Hoogte: 24 mm

Breedte: 400 mm

Diepte: 90 mm

Materiaal: Verzinkt plaatstaal

Finish: Zinc Plated

Kleur: Unpainted

Dikte: 1.75 mm



[nVent.com](https://www.nVent.com)

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN RAYCHEM SCHROFF

TRACER