


FLEXBUS ALUMINIUM GEPERFOREERD PROFIEL

CATALOG NUMBER

FLEXALPROF2M



CERTIFICATIONS



FEATURES

Optional brackets are available

Factory-punched head holes for quick assembly

RoHS compliant

PRODUCTKENMERKEN

Article Number: 508100

Material: Aluminium

A: 12,5 mm

Hole Size (HS): 8 mm

Height (H): 15 mm

Length (L): 2000 mm

Width (W): 35 mm


Unit Weight: 0,9 kg

ADDITIONAL PRODUCT DETAILS

Support kit and aluminum profile are sold separately.

When cable tray is used, we recommend installing a Flexbus Support at each extremity, in order to protect the Flexbus Conductor against potential sharp edges of the cable tray.

DIAGRAMS



WAARSCHUWING

Producten van nVent moeten worden geïnstalleerd en gebruikt op de manier zoals is aangegeven in de nVent productinformatiebladen en trainingsmaterialen. U kunt de productinformatiebladen downloaden van www.nvent.com of opvragen bij uw nVent-klantenservice. Door onjuist installeren, verkeerd gebruik, verkeerde toepassing of enige andere handeling in strijd met de instructies en waarschuwingen van nVent kan het product mogelijk niet correct werken, ernstig of fataal letsel en materiële schade veroorzaken en/of uw garantie ongeldig maken.

Noord-Amerika
+1.800.753.9221
Option 1 – Customer Care
Option 2 – Technical Support

Europa
Netherlands:
+31 800-0200135
France:
+33 800 901 793

Europa
Germany:
800 1890272
Other Countries:
+31 13 5835404

APAC
Shanghai:
+ 86 21 2412 1618/19
Sydney:
+61 2 9751 8500