

Eaton 9PX3000RT

Catalog Number: 9PX3000RT

Eaton 9PX UPS, 2U, 3000 VA, 2700 W, L5-30P input, Outputs: (6) 5-20R, (1) L5-30R, 120V

General specifications



Product Name
Eaton 9PX UPS

Catalog Number
9PX3000RT

UPC
743172081285

Product Length/Depth
23.8 in

Product Height
3.4 in

Product Width
17.3 in

Product Weight
63.1 lb

Warranty
3 year on electronics, 2 year on battery

Compliances
IEC 62040-2 Cat C1
CISPR22 Class B
FCC part 15 Class B
VCCI Class B
CE Marked

Certifications
cULus Listed
NOM
ENERGY STAR certified

defaultTaxonomyAttributeLabel

Type

UPS

Topology

Online/Double-conversion

Form factor

Rack/tower

Rack size

2U

Color

Black/silver

VA rating

3000 VA

Wattage

2700 W

Rack mounting kit

Yes

Package contents

9PX3000RT UPS
4-post rail kit
Safety manual
User manual
Tower pedestals
RS-232 serial cable
USB cable
Intelligent Power Software
Suite CD

Internal bypass

Yes

Input connection

L5-30P

Input cord length

8 ft

Input nominal voltage

120V default (100/110/120/125V)

Input frequency range

60 Hz: 50–70 Hz, 50 Hz: 40–60 Hz

Resources

Brochures

[Eaton 9PX 700-3000 VA UPS brochure](#)

[Eaton UPS and battery services - EN](#)

[Eaton UPS Services Quick Guide - EN](#)

Drawings

[Battery Integration System Pro-E drawing](#)

[Eaton 9PX UPS 2000-3000 VA 120V outline drawing](#)

[Eaton 9PX UPS 9PX3000RT technical drawing](#)

Manuals and user guides

[9PX battery integration system user guide](#)

[9PX 2-post rack kit user guide](#)

[9PX 700-3000 VA 2U UPS user guide](#)

Specifications and datasheets

[9PX 700-3000 VA UPS technical specification](#)

[Eaton 9PX UPS guide specification: 700-3000 VA](#)

[Eaton Specification Sheet - 9PX3000RT](#)

Input power factor

>0.99 typical

Receptacle

(6) 5-20R, (1) L5-30R

Number of Outputs 5-20R

6

Number of Outputs L5-30R

1

Output waveform

True sine wave

Voltage

120V

Output nominal voltage

120V default (100/110/120/125V)

Runtime graph

[View runtime graph](#)

Battery management

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

Battery replacement

Hot-swappable internal batteries and extended battery modules (EBMs)

Battery type

Sealed, lead-acid

Extended battery capability

Add up to 4 extended battery modules (EBM). Part number 9PXEBM72RT

Standard factory warranty

3-YEAR FACTORY
WARRANTY

- 3 years
- Parts, electronics and batteries coverage
- Standard ground shipping
- Technical support

Extended service plans

ADVANCED DEPOT
EXCHANGE

- 5-year depot repair:
9SW5Y-3000UC
- Expedited parts coverage
for 5 years
- Parts, electronics and UPS
batteries coverage
- Next business day
shipping
- Technical support
- 5-YEAR ON-SITE PLAN:
WFLN75XX-6009UC
- On-site parts and labor
coverage for years 5
- Parts, electronics and UPS
batteries coverage
- 24x7 on-site labor
coverage, next-day
response
- Next-day shipping
- Technical support

Communication

MiniSlot + 1 USB port + 1 serial RS232 port + 1 mini-terminal
block for remote ON/OFF + 1 mini-terminal block for remote
power off + 1 mini-terminal block for output relay Communication
slot

Expansion slots

(1) Mini-Slot (MS) expansion
port. The following optional
connectivity cards may be
ordered separately.
Gigabit Network Card part
number: NETWORK-M3
Modbus card part number:
INDGW-M2
Relay card part number:
RELAY-MS

Software compatibility

Intelligent Power Software Suite

User interface

Graphical display, 5-button programmable menu

Altitude

0-1500m (0° to 40°C), 1500-3000m (0° to 35°C)

BTU Rating

Online: 844, Battery: 1462

Noise level

<47 dB at 1 meter

Relative humidity

0-96% non-condensing

Temperature range

0° to 40°C (32° to 104°F)

Efficiency

91%

Max number of battery packs

4

Output frequency

50/60 Hz

Output power factor

0.9

Output voltage range

±1% steady-state

Runtime at full load

5 min



Eaton Corporation plc

Eaton House

30 Pembroke Road

Dublin 4, Ireland

Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia