

Eaton RS2-11-C10

Catalog Number: RS2-11-C10

Eaton RS-Titan non-contact door interlock safety switch, Magnetic Reed Switch, Polyamide enclosure, 300 mA max DC, 1 Normally Open and 1 Normally Closed, 300 mA at 24 Vdc, 33 Ft. (10m) Cable, < 10% accuracy, 33 Ft. (10m)

General specifications



Product Name	Catalog Number
Eaton RS-Titan non-contact door interlock safety switch	RS2-11-C10
	UPC
	786685886367
Product Length/Depth	Product Height
0.94 in	2 in
Product Width	Product Weight
0.44 in	0.875 lb
Warranty	Compliances
1 year	CE Marked
Certifications	Catalog Notes
UL Listed	0

defaultTaxonomyAttributeLabel

Type

Mechanical Limit Switches

Contact Rating

300 mA at 24 Vdc

Cable type

Polyvinyl Chloride (PVC)

Accuracy

< 10%

Enclosure material

Polyamide

Cord length

396 ft

Connection

33 ft (10m) cable

Contact configuration

1 NO-1 NC

Switch type

Magnetic reed switch

Operating temperature - max

131 °F

Operating temperature - min

14 °F

Environmental rating

IP67, IP69K

Maximum DC current

300 mA

Resources

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - RS2-11-C10](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia