



BU cover 30 mm for ET 200SP motor starter for protection of empty slots

product category	Accessories
product designation	Base Unit cover 30 mm
design of the product	for protection of empty slots, 30 mm
product type designation	BaseUnit cover

General technical data

product function	Zubehör
degree of pollution	2
shock resistance	6g / 11 ms
Substance Prohibitance (Date)	04/15/2016

Installation/ mounting/ dimensions

mounting position	vertical, horizontal, flat
fastening method	pluggable on BaseUnit
height	135 mm
width	30 mm
depth	60 mm

Ambient conditions

ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C

Approvals Certificates

General Product Approval	EMV
--------------------------	-----

[Confirmation](#)



EG-Konf.



UL



RCM

Test Certificates	Marine / Shipping	other
-------------------	-------------------	-------

[Type Test Certificates/Test Report](#)



ABS



BUREAU
VERITAS



DNV



LRS

[Confirmation](#)

Environment

[Environmental Confirmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RK1908-1CA00-0BP0>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RK1908-1CA00-0BP0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RK1908-1CA00-0BP0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RK1908-1CA00-0BP0&lang=en



last modified:

1/7/2021 