
Specifications

Eaton 215645



Catalog Number: 215645

Eaton Moeller series xPole - Busbar. EV busbars 3Ph., 9HP, 63A for PLS. CLS. PKN., PFIM, PFHM, PFNM

General specifications

Product Name	**Catalog Number**
Eaton Moeller series busbar	215645
Model Code	**EAN**
EVG-3PHAS/9MODUL	9010238140318
Product Length/Depth	**Product Height**
140 mm	30 mm
Product Width	**Product Weight**
10 mm	0.063 kg
Compliances	**Certifications**
RoHS conform	CE

Powering Business Worldwide

Product specifications

Used with

PLS. CLS. PKN., PFIM, PFHM, PFNM

Busbar

EVG

Type

Busbar

EVG

Features

Insulated

Accessory/spare part type

Busbar for residual current circuit breakers

Busbar for combined residual current/power circuit breaker

Busbar for miniature circuit breaker

Electric connection type

Fork

Rated surge voltage

4 KV

Rated uninterrupted current (Iu)

63 A

Suitable for number of devices

3

Number of poles

Three-pole

Color

Other

Rated short-time withstand current (Icw)

0 kA

Cross section

10 mm²

Number of modular spacings

9

Number of phases

3

Pitch dimensions

0 mm

Resources

Declarations of conformity

DA-DC-03_EVG

Drawings

eaton-busbar-3d-drawing.jpg

Specifications and datasheets

Eaton Specification Sheet - 215645

Rated operational voltage (Ue) - max

500 V

Rated conditional short-circuit current (Iq)

25 kA

Functions

Busbar

Suitable for

3 devices

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Eaton.com/socialmedia