

Eaton 052302

Catalog Number: 052302

Eaton Moeller® series DILEM Contactor, 230 V 50/60 Hz, 3 pole, 380 V 400 V, 4 kW, Contacts N/O = Normally open= 1 N/O, Screw terminals, AC operation

General specifications



Product Name

Eaton Moeller® series DILEM Mini
contactor

Catalog Number

052302

Model Code

DILEM-10(230V50/60HZ)

EAN

4015080523024

Product Length/Depth

51 mm

Product Height

58 mm

Product Width

45 mm

Product Weight

0.17 kg

Certifications

CE
CSA
IEC/EN 60947-4-1
CSA Class No.: 3211-04
VDE 0660
UL
UL File No.: E29096
UL Category Control No.: NLDX
UL 508
CSA File No.: 012528
CSA-C22.2 No. 14-05
IEC/EN 60947

Catalog Notes

Also tested according to AC-3e.

Product specifications

Number Of Poles

Three-pole

Type

Full voltage non-reversing

Voltage rating

400 V

Features

Positive operating contacts to EN 60947-5-1 appendix L, including auxiliary contact module

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Resources

Catalogs

Switching and protecting motors - catalog

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Product Range Catalog Switching and protecting motors](#)

Characteristic curve

[eaton-contactors-short-time-loading-dilm-characteristic-curve.eps](#)

[eaton-contactors-component-dilm-characteristic-curve-003.eps](#)

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

Declarations of conformity

[DA-DC-00004812.pdf](#)

[DA-DC-00004788.pdf](#)

Drawings

[eaton-contactors-dilem-dimensions.eps](#)

[eaton-contactors-diler-dimensions-005.eps](#)

[eaton-contactors-diler-dimensions-004.eps](#)

[eaton-tripping-devices-mounting-diler-contactor-relay-symbol.eps](#)

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

eCAD model

[ETN.052302.edz](#)

Installation instructions

[IL03407009Z](#)

mCAD model

[DA-CS-dil_em](#)

[DA-CD-dil_em](#)

Specifications and datasheets

[Eaton Specification Sheet - 052302](#)

System overview

[eaton-contactors-accessory-dilem-system-overview.eps](#)

Wiring diagrams

[eaton-contactors-contact-dilm-wiring-diagram.eps](#)

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Fitted with:

Auxiliary contact

Operating frequency

9000 mechanical Operations/h

Pollution degree

3

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Rated impulse withstand voltage (Uimp)

6000 V AC

Utilization category

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running

Connection

Screw terminals

Ambient operating temperature - max

50 °C

Ambient operating temperature - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient operating temperature (enclosed) - min

-25 °C

Ambient storage temperature - max

80 °C

Ambient storage temperature - min

-40 °C

Assigned motor power at 115/120 V, 60 Hz, 1-phase

0.5 HP

Assigned motor power at 200/208 V, 60 Hz, 3-phase

2 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase

1.5 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase

3 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase

5 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase

5 HP

Conventional thermal current I_{th} (1-pole, enclosed)

40 A

Conventional thermal current I_{th} (3-pole, enclosed)

16 A

Conventional thermal current I_{th} at 55°C (3-pole, open)

19 A

Conventional thermal current I_{th} of auxiliary contacts (1-pole, open)

10 A

Conventional thermal current I_{th} of main contacts (1-pole, open)

50 A

Equipment heat dissipation, current-dependent P_{vid}

1.2 W

Heat dissipation capacity P_{diss}

0 W

Heat dissipation per pole, current-dependent P_{vid}

0.4 W

Switching time (AC operated, N/O, with auxiliary contact module, closing delay)

45 ms

Application

Mini Contactors for Motors and Resistive Loads

Product category

Contactors

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Terminals

Screw terminals

Arcing time

12 ms at 690 V AC

Electrical connection type of main circuit

Screw connection

Screwdriver size

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver
2, Terminal screw, Pozidriv screwdriver

Voltage type

AC

Degree of protection

IP20

Mounting position

As required (except vertical with terminals A1/A2 at the bottom)

Number of auxiliary contacts (normally closed contacts)

0

Number of auxiliary contacts (normally open contacts)

1

Number of contacts (normally closed) as main contact

0

Number of main contacts (normally open contact)

3

Rated breaking capacity at 220/230 V

90 A

Rated breaking capacity at 380/400 V

90 A

Rated breaking capacity at 500 V

64 A

Rated breaking capacity at 660/690 V

42 A

Rated control supply voltage (Us) at AC, 50 Hz - max

230 V

Rated control supply voltage (Us) at AC, 50 Hz - min

230 V

Rated control supply voltage (Us) at AC, 60 Hz - max

230 V

Rated control supply voltage (Us) at AC, 60 Hz - min

230 V

Coil voltage

230 Vac, 50-60 Hz

Overvoltage category

III

Control circuit reliability

$< 2 \lambda$, < 1 failure at 100,000,000 Operations (at $U_e = 24$ V DC,
 $U_{min} = 17$ V, $I_{min} = 5.4$ mA)

Duty factor

100 %

Changeover time

16 - 21 ms

Number of contacts

1 NO

Lifespan, mechanical

7,000,000 Operations (Coil 50/60 Hz)

200,000 Operations (at 240 V, AC-15)

150,000 Operations (at 240 V, DC, L/R = 50 ms: 2 contacts in
series 0.5 A)

10,000,000 Operations

Pick-up voltage

0.85 - 1.1 V AC x U_c (voltage tolerance - dual frequency coil
50/60 Hz)

Power consumption, pick-up, 50 Hz

26 W, AC, Dual-frequency coil at 50 Hz

30 VA, AC, Dual-frequency coil at 50 Hz

Safe isolation

300 V AC, Between auxiliary contacts, According to EN 61140

300 V AC, Between coil and contacts, According to EN 61140

300 V AC, Between the contacts, According to EN 61140

300 V AC, Between coil and auxiliary contacts, According to EN
61140

Power consumption, pick-up, 60 Hz

24 W, AC, Dual-frequency coil at 60 Hz

29 VA, AC, Dual-frequency coil at 60 Hz

Screw size

M3.5, Terminal screw

Power consumption, sealing, 50 Hz

1.8 W, Coil in a cold state and 1.0 x U_s

5.4 VA, Coil in a cold state and 1.0 x U_s

Power consumption, sealing, 60 Hz

1.8 W, AC, Dual-frequency coil at 60 Hz

1.8 W, Coil in a cold state and 1.0 x U_s

5.4 VA, Coil in a cold state and 1.0 x U_s

3.9 VA, AC, Dual-frequency coil at 60 Hz

Rated operational current (I_e)

2.5 A at 24 V, DC L/R ≤ 15 ms (with 1 contact in
series)

1.5 A at 100 V, DC L/R ≤ 15 ms (with 3 contacts in
series)

0.5 A at 220 V, DC L/R ≤ 15 ms (with 3 contacts in
series)

2.5 A at 60 V, DC L/R ≤ 15 ms (with 2 contacts in
series)

Switching capacity (auxiliary contacts, general use)

0.5 A, 250 V DC, (UL/CSA)

10 A, 600 V AC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

P300, DC operated (UL/CSA)

A600, AC operated (UL/CSA)

Terminal capacity (flexible with ferrule)

1 x (0.75 - 1.5) mm²

2 x (0.75 - 1.5) mm²

Shock resistance

10 g, N/O main contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

20 g, N/O auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

10 g, N/O main contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

8 g, N/O auxiliary contact, Basic unit without auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

20 g, N/C auxiliary contact, Basic unit with auxiliary contact module, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Terminal capacity (solid)

2 x (0.75 - 2.5) mm²

1 x (0.75 - 2.5) mm²

Terminal capacity (solid/stranded AWG)

18 - 14

Switching capacity (main contacts, general use)

15 A, Maximum motor rating (UL/CSA)

Tightening torque

1.2 Nm, Screw terminals

Rated control supply voltage (Us) at DC - max

0 V

Rated control supply voltage (Us) at DC - min

0 V

Rated insulation voltage (Ui)

690 V

Rated making capacity up to 440 V (cos phi to IEC/EN 60947)

110 A

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V

22 A

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V

6 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V

3 A

Rated operational current (I_e) at AC-15, 500 V

1.5 A

Rated operational current (I_e) at AC-3, 220 V, 230 V, 240 V

9 A

Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V

9 A

Rated operational current (I_e) at AC-3, 440 V

9 A

Rated operational current (I_e) at AC-3, 500 V

6.4 A

Rated operational current (I_e) at AC-3, 660 V, 690 V

4.8 A

Rated operational current (I_e) at AC-4, 220 V, 230 V, 240 V

6.6 A

Rated operational current (I_e) at AC-4, 400 V

6.6 A

Rated operational current (I_e) at AC-4, 440 V

6.6 A

Rated operational current (I_e) at AC-4, 500 V

5 A

Rated operational current (I_e) at AC-4, 660 V, 690 V

3.4 A

Rated operational current (I_e) at DC-1, 110 V

20 A

Rated operational current (I_e) at DC-1, 12 V

20 A

Rated operational current (I_e) at DC-1, 220 V

20 A

Rated operational current (I_e) at DC-1, 24 V

20 A

Rated operational current (I_e) at DC-1, 60 V

20 A

Rated operational current for specified heat dissipation (I_n)

9 A

Rated operational power at AC-3, 240 V, 50 Hz

2.5 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

4 kW

Rated operational power at AC-3, 415 V, 50 Hz

4.3 kW

Rated operational power at AC-4, 220/230 V, 50 Hz

1.5 kW

Rated operational power at AC-4, 240 V, 50 Hz

1.8 kW

Rated operational power at AC-4, 380/400 V, 50 Hz

3 kW

Rated operational power at AC-4, 415 V, 50 Hz

3.1 kW

Rated operational power at AC-4, 440 V, 50 Hz

3.3 kW

Rated operational power at AC-4, 500 V, 50 Hz

3 kW

Rated operational power at AC-4, 660/690 V, 50 Hz

3 kW

Rated operational power (NEMA)

3.7 kW

Rated operational voltage (Ue) at AC - max

690 V

Resistance per pole

9.18 m Ω

Static heat dissipation, non-current-dependent Pvs

1.8 W

Stripping length (main cable)

8 mm

Switching time (AC operated, make contacts, closing delay) - max

21 ms

Switching time (AC operated, make contacts, closing delay) - min

14 ms

Switching time (AC operated, make contacts, opening delay) - max

18 ms

Switching time (AC operated, make contacts, opening delay) - min

8 ms

Short-circuit current rating (basic rating)

5 kA, SCCR (UL/CSA)

45 A, max. Fuse, SCCR (UL/CSA)

Short-circuit protection

10 A fast, Max. Fuse 500V, Auxiliary contacts, Short-circuit rating without welding

PKZM0-4, Maximum overcurrent protective device, Short-circuit protection only, Auxiliary contacts, Short-circuit rating without welding

6 A gG/gL, Max. Fuse 500V, Auxiliary contacts, Short-circuit rating without welding

Suitable for

Also motors with efficiency class IE3

Short-circuit protection rating (type 1 coordination) at 500 V

20 A gG/gL

Short-circuit protection rating (type 2 coordination) at 500 V

10 A gG/gL

Conventional thermal current i_{th} at 40°C (3-pole, open)

22 A

Conventional thermal current i_{th} at 50°C (3-pole, open)

20 A

Rated operational power at AC-3, 440 V, 50 Hz

4.6 kW

Rated operational power at AC-3, 500 V, 50 Hz

4 kW

Rated operational power at AC-3, 690 V, 50 Hz

4 kW

Actuating voltage

230 V 50/60 Hz

Altitude

Max. 2000 m

Operating voltage at AC, 50 Hz - min

24 V

Operating voltage at AC, 50 Hz - max

690 V

Operating voltage at AC, 60 Hz - min

24 V

Operating voltage at AC, 60 Hz - max
690 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.
All other trademarks are property of their respective owners.



Eaton.com/socialmedia