

# Specifications



## Eaton CHM1DNIU

Eaton Bussmann series CHM modular fuse holder, 600V (UL), 690V (IEC), 30A (UL), 32A (IEC), 200 kAIC, Modular fuse holder, Single-pole - CHM1DNIU

### General specifications

|                             |                                               |
|-----------------------------|-----------------------------------------------|
| <b>PRODUCT NAME</b>         | Eaton Bussmann series CHM modular fuse holder |
| <b>CATALOG NUMBER</b>       | CHM1DNIU                                      |
| <b>UPC</b>                  | 051712362764                                  |
| <b>EAN</b>                  | 51712362764                                   |
| <b>PRODUCT LENGTH/DEPTH</b> | 0.001 mm                                      |
| <b>PRODUCT HEIGHT</b>       | 0.001 mm                                      |
| <b>PRODUCT WIDTH</b>        | 0.001 mm                                      |
| <b>PRODUCT WEIGHT</b>       | 113 g                                         |
| <b>WARRANTY</b>             | Not Applicable                                |
| <b>COMPLIANCES</b>          | Contact factory<br>RoHS Compliant             |
| <b>CERTIFICATIONS</b>       | Contact Manufacturer                          |

## Electrical rating

|                         |                         |
|-------------------------|-------------------------|
| <b>AMPERAGE RATING</b>  | 30A (UL), 32A (IEC)     |
| <b>INTERRUPT RATING</b> | 200 kAIC                |
| <b>VOLTAGE RATING</b>   | 600 V (UL), 690 V (IEC) |

## General information

|                  |                                 |
|------------------|---------------------------------|
| <b>USED WITH</b> | For use with 10 mm X 38 mm fuse |
|------------------|---------------------------------|

## Physical details

|                                    |             |
|------------------------------------|-------------|
| <b>NUMBER OF POLES</b>             | Single-pole |
| <b>OPERATING TEMPERATURE - MAX</b> | 90 °C       |
| <b>OPERATING TEMPERATURE - MIN</b> | -20 °C      |
| <b>WIRE SIZE</b>                   | #18-4 AWG   |

## Resources

|                                      |                                                                                       |
|--------------------------------------|---------------------------------------------------------------------------------------|
| <b>DECLARATIONS OF CONFORMITY</b>    | <a href="#">CE Modular fuse-holders</a><br><a href="#">UKCA Modular fuse-holders</a>  |
| <b>DRAWINGS</b>                      | <a href="#">Eaton Power Distribution CHM Modular Fuse Holder CAD Drawing CHM1DNIU</a> |
| <b>MULTIMEDIA</b>                    | <a href="#">Bussmann series Fuseology</a>                                             |
| <b>SPECIFICATIONS AND DATASHEETS</b> | <a href="#">Eaton Specification Sheet - CHM1DNIU</a>                                  |
| <b>TECHNICAL DATA SHEETS</b>         | <a href="#">720147 10 x 38 mm Modular fuse holder</a>                                 |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

