

Specifications

Eaton KTK-R-20

Eaton Bussmann Series Class CC fuse, KTK-R, fast-acting, dual-element current limiting fuse, 20 A, rejection style fuse, interrupting rating of 200kA at 600Vac

General specifications

PRODUCT NAME	Eaton Bussmann series KTK-R fuse
CATALOG NUMBER	KTK-R-20
UPC	051712420716
PRODUCT LENGTH/DEPTH	1.5 in
PRODUCT HEIGHT	0.41 in
PRODUCT WIDTH	0.41 in
PRODUCT WEIGHT	0.18 lb
WARRANTY	Not Applicable
COMPLIANCES	CE Marked RoHS Compliant
CERTIFICATIONS	UL Listed CSA Certified

Product specifications

AMPERAGE RATING	20 A
NUMBER OF ELEMENTS	Dual
CLASS	Class CC
INTERRUPT RATING	200 kAIC
FUSE INDICATOR	Non-indicating
CONNECTION	Ferrule end x ferrule end Ferrule
RESPONSE TIME	See time current curve
MATERIAL	Melamine tube
PACKAGING TYPE	Standard
QUANTITY	10
VOLTAGE RATING	600 V
TYPE	Current-limiting fast-acting fuse
SPECIAL FEATURES	Rejection style
APPLICATION	Industrial controls panels and machinery, street lighting, general lighting, capacitors and distribution

Resources

	Low Voltage Branch Circuit Fuse Chapter
CATALOGS	Bussmann Full Line Catalog Bussmann series complete full line catalog no. 1007
CERTIFICATION REPORTS	Eaton Bussmann EU Declaration of conformity 93-68-EEC2000
MULTIMEDIA	Bussmann series Fuseology
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - KTK-R-20 KTK-R Spec Sheet
TECHNICAL DATA SHEETS	KTK-R-20~CLASS CC FAST ACTING FUSE CLASS CC

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

