


<https://www.wago.com/812-113>



Common potential terminal block, 812 Series, CAGE CLAMP®

Electrical data

Ratings per IEC/EN

Nominal voltage (III/3)	1000 V
Rated impulse withstand voltage (III / 3)	6 kV
Rated current	96 A
Legend (ratings)	(III / 3) $\triangleq$ Overvoltage category III / Pollution degree 3

Ratings per IEC/EN – Notes

Rated current (note)	Current carrying capacity: With a maximum total current of 96 A, the clamping units of the busbar terminal block can be loaded with the rated current of the conductor cross-sections approved. This only applies when (10 x 3) mm busbars are used.
----------------------	--

Connection data

Clamping units	3
Total number of potentials	1
Number of levels	1

Connection 1

Connection technology	CAGE CLAMP®
Actuation type	Operating tool
Connectable conductor materials	Copper
Solid conductor	1.5 ... 16 mm² / 14 ... 6 AWG
Fine-stranded conductor	1.5 ... 16 mm² / 14 ... 6 AWG
Strip length	12 mm / 0.47 inches
Wiring direction	Front-entry wiring



Physical data	
Width	38 mm / 1.496 inches
Height	42.5 mm / 1.673 inches
Depth	43.5 mm / 1.713 inches

Material data	
Note (material data)	Information on material specifications can be found here
Color	red
Material group	I
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.851 MJ
Weight	42 g

Environmental requirements	
Continuous operating temperature	-35 ... +85 °C

Commercial data	
Product Group	12 (Matrix Patch Board)
eCl@ss 10.0	27-14-11-46
eCl@ss 9.0	27-14-11-46
ETIM 9.0	EC000001
ETIM 8.0	EC000001
PU (SPU)	12 pcs
Packaging type	Box
Country of origin	PL
GTIN	4045454014919
Customs tariff number	85369010000

Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates		
General approvals		Declarations of conformity and manufacturer's declarations
Approval	Standard	Certificate Name
CCA DEKRA Certification B.V.	EN 60947	NTR NL-7153
CSA CSA Group	C22.2 No. 158	2131504
KEMA/KEUR DEKRA Certification B.V.	EN 60947	2160584.49
UL Underwriters Laboratories Inc.	UL 1059	UL-US- L45172-6187154-31109002-1
		Approval
		EU-Declaration of Confor- mity WAGO GmbH & Co. KG
		UK-Declaration of Confor- mity WAGO GmbH & Co. KG



Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 812-113

Download icon

Documentation

Additional Information

Technical Section

pdf

2246.92 KB

Download icon

Bid Text

812-113

18.07.2019

xml

3.79 KB

Download icon

812-113

18.07.2019

docx

15.18 KB

Download icon

CAD/CAE-Data

CAD data

2D/3D Models 812-113

Download icon

CAE data

EPLAN Data Portal 812-113

Download icon

WSCAD Universe 812-113

Download icon

ZUKEN Portal 812-113

Download icon

1 Compatible Products

1.1 Optional Accessories

1.1.1 Cover

1.1.1.1 Cover



Item No.: 284-400
Finger guard; touchproof cover protects unused conductor entries; yellow

1.1.2 Ferrule

1.1.2.1 Ferrule



Item No.: 216-209
Ferrule; Sleeve for 10 mm² / AWG 8; insulated; electro-tin plated; red



Item No.: 216-109
Ferrule; Sleeve for 10 mm² / AWG 8; un-insulated; electro-tin plated



Item No.: 216-210
Ferrule; Sleeve for 16 mm² / AWG 6; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; blue



Item No.: 216-110
Ferrule; Sleeve for 16 mm² / AWG 6; un-insulated; electro-tin plated; brown metallic



Item No.: 216-208
Ferrule; Sleeve for 6 mm² / AWG 10; insulated; electro-tin plated; electrolytic copper; gastight crimped; acc. to DIN 46228, Part 4/09.90; yellow



Item No.: 216-108
Ferrule; Sleeve for 6 mm² / AWG 10; un-insulated; electro-tin plated; silver-colored

1.1.3 N-busbar

1.1.3.1 Busbar



Item No.: 210-133


Busbar; tin-plated; 1000 mm long; Cu 10 mm x 3 mm; white

Installation Notes

Installation



Snapping a ground busbar terminal block onto the N-busbar.



Conductor termination (16 mm²/6 AWG):
Open the clamping unit with an operating tool when terminating solid, stranded and fine-stranded conductors.