

# Stelsysteem groot volume, vert.

## CATALOGUSNUMMER

**A3003YZVM**



Large-Volume Purging/Pressurization System supplies one or more enclosures, up to 90 cubic feet total volume, with a protective gas supply, thus allowing the use of general-purpose enclosures in certain Class 1, Division 1 and 2 hazardous locations.

## INDUSTRIENORMEN

Classified by Underwriters Laboratories, NFPA 496-1993

(Volume up to 90 cubic feet)

3003 LPS

NEC Type Y Class 1, Division 1, Groups A, B, C and D / Zone 1 Groups IIA, IIB and IIC to Division 2 / Zone 2

NEC Type Z Class I, Division 2, Groups A, B, C and D / Zone 2 Groups IIA, IIB and IIC to Nonhazardous

## KENMERKEN

Vertical mount (VM) or horizontal mount (HM)

90 cubic feet maximum enclosure volume

System face plate and mounting plate: Type 316L stainless steel

Regulator body: zinc with enamel finish

Manifold body: anodized aluminum with Type 316 stainless steel valves

Enclosure pressure gauge: aluminum with enamel finish

Gas supply gauge: poly case and nickel-plated tube

Enclosure protection vent—90 degree

Rapid exchange control valve

Enclosure supply and enclosure reference bulkhead fittings: Type 316 stainless steel

Fastener hardware

## PRODUCTKENMERKEN

Hoogte: 242mm

Breedte: 140mm

Materiaal: Roestvrij staal 316L

Afwerking: Getrommeld

Dikte: 1.98mm

Volume: 2.55m<sup>3</sup>

Gewicht: 4.54kg

## WAARSCHUWING

---

nVent-producten moeten alleen worden geïnstalleerd en gebruikt zoals aangegeven in de instructiebladen en trainingsmateriaal van nVent. Instructiebladen zijn beschikbaar op [www.nvent.com](http://www.nvent.com) en bij uw nVent klantenservicevertegenwoordiger. Onjuiste installatie, misbruik, verkeerde toepassing of ander falen om de instructies en waarschuwingen van nVent volledig te volgen, kan leiden tot productstoringen, schade aan eigendommen, ernstig lichamelijk letsel en de dood en/of uw garantie ongeldig maken.



Ons krachtige merkenportfolio:

**CADDY   ERICO   HOFFMAN   ILSCO   SCHROFF   TRACHTE**