We connect and protect

SpectraCool Slim Fit S06 voor binnengebruik, 300 W, 230 V C, lichtgrijs, staal

CATALOGUSNUMMER

S060326G031

SpectraCool SlimFit Air Conditioners are designed with three space-saving mounting options to maximize footprint. They have been developed to meet the requirements of worldwide industrial customers, easy to specify and easy to use. From filterless operation to global certifications, the SpectraCool Slim Fit Air Conditioner makes automation cooling easy for system designers and operations maintenance teams around the world.

Select units come with a Commboard for Remote Access Control (RAC), an integrated, parametric controller designed to work seamlessly with our enclosure air conditioner units for the purpose of remotely monitoring and managing anywhere from a single unit to an entire network of Spectra cool air conditioners from virtually anywhere in the world with a secure internet connection. Ensure that your systems are always running at optimal temperature levels, increase productivity and improve overall system reliability.

INDUSTRIENORMEN

UL/cUL Listed Type 12; File No.SA6453

CE, EAC, RoHS

Cooling performance tested by TÜV SÜD Germany, according to DIN EN 14511

IP 54 internal loop, IP 34 external loop

KENMERKEN

Les unités de contrôle d'accès à distance peuvent contrôler jusqu'à 2 capteurs de température et 10 alarmes. Ils peuvent contrôler plusieurs protocoles de communication : SNMP, Modbus TCP, Ethernet/IP et Profinet.

Slim Fit Design with three mounting options; fully recessed, partial recessed and surface mount

Aesthetic design plastic cover to optimize air flow

R134a refrigerant

Voltage: 230 V (50/60 Hz), 115 V (50/60 Hz) and 400/460 V 3-phase (50/60 Hz)

Operating temperature range from 50 F / 10 C to 131 F / 55 C

Easy filter replacement for extremely dusty environments

Dust resistant coils for filterless operation
Active condensate management to prevent dripping water
Energy efficient rotary compressor
Terminal block power input
Standard cutout dimension for easy exchange
Every unit functionally tested before shipping
Standard Air Conditioners are compatible with an enclosure door switch
Mounting hardware, gaskets and user manual furnished with the unit

PRODUCTKENMERKEN

Nominale capaciteit BTU/u: 1000Btu/h
Nominale capaciteit watt: 300W
Nominale spanning: 230V
Hoogte: 549mm
Breedte: 279mm
Diepte: 140mm
Dikte: 1.21mm
Bedrijfstemperatuur: 10 – 55°C
Max. stroomsterkte: 6A
Toegangsbeheer op afstand: Nee
Materiaal: Plaatstaal
Afwerking: Gepoedercoat
Kleur: Lichtgrijs
Kleurcode: RAL 7035

WAARSCHUWING

nVent-producten moeten alleen worden geïnstalleerd en gebruikt zoals aangegeven in de instructiebladen en trainingsmateriaal van nVent. Instructiebladen zijn beschikbaar op www.nvent.com en bij uw nVent klantenservicevertegenwoordiger. Onjuiste installatie, misbruik, verkeerde toepassing of ander falen om de instructies en waarschuwingen van nVent volledig te volgen, kan leiden tot productstoringen, schade aan eigendommen, ernstig lichamelijk letsel en de dood en/of uw garantie ongeldig maken.

Ons krachtige merkenportfolio:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2025 nVent. Alle nVent-merken en -logo's zijn eigendom van of in licentie gegeven door nVent Services GmbH of haar gelieerde ondernemingen. Alle andere handelsmerken zijn het eigendom van hun respectieve eigenaren. nVent behoudt zich het recht voor om specificaties zonder kennisgeving te wijzigen.

Dit document is door het systeem gegenereerd.