# Specifications



**Photo is representative**

## Eaton SL7-AP24-E

Acoustic Module, SL7, 70 mm, Continuous tone, 2 modules, External actuation, 92A max., 24 Vac/Vdc, Black, 100 dB, 2800 Hz, Internal potentiometer, 2 assigned inputs, (1), UL type 4, 4X, 13 , IP66

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton SL7 stacklight acoustic module |
| **CATALOG NUMBER** | SL7-AP24-E |
| **EAN** | 4015081678297 |
| **PRODUCT LENGTH/DEPTH** | 3.5 in |
| **PRODUCT HEIGHT** | 3 in |
| **PRODUCT WIDTH** | 3 in |
| **PRODUCT WEIGHT** | 0.25 lb |
| **WARRANTY** | 2 year |
| **COMPLIANCES** | CE Marked |
| **CERTIFICATIONS** | CSA Certified<br>UL Listed<br>UL 508<br>cULus Listed<br>CSA Std. C22.2 No. 14-10<br>CSA Std. C22.2 No. 94-91<br>CSA Class No. NKCR7<br>UL Listed file E29184<br>IEC Rated |
| **CATALOG NOTES** | 0 |
| **PRODUCT TYPE** | Stacklight acoustic module |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **TYPE** | 70 mm |
| **ENVIRONMENTAL RATING** | IP66 |
| **ACCESSORIES** | Internal potentiometer |
| **VOLTAGE RATING** | 24 Vac/Vdc |
| **FREQUENCY RATING** | 2800 Hz |
| **RATED OPERATIONAL CURRENT** | 92 A maximum |
| **DECIBEL** | 100 dB |
| **ACTUATOR** | External actuation |
| **NUMBER OF INPUTS** | 2 assigned |
| **QUANTITY** | 1 |
| **ENCLOSURE** | UL type 4, 4X, 13 |
| **SERIES** | SL7 |
| **COLOR** | Black |
| **MODEL** | Continuous tone |
| **NUMBER OF MODULES** | 2 |

## Resources

| | |
|---|---|
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - SL7-AP24-E |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.