# Specifications



Photo is representative





## Eaton 236707

Eaton Moeller series xPole - PKN6/M RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB, 25A, 30mA, MCB trip curve C, 1pole+N, RCCB trip char.: A

| General specifications | |
|---|---|
| **PRODUCT NAME** | Eaton Moeller series xPole - PKN6/M RCBO - residual-current circuit breaker with overcurrent protection |
| **CATALOG NUMBER** | 236707 |
| **MODEL CODE** | PKN6-25/1N/C/003-A-MW |
| **EAN** | 4015082367077 |
| **PRODUCT LENGTH/DEPTH** | 80 mm |
| **PRODUCT HEIGHT** | 73 mm |
| **PRODUCT WIDTH** | 35 mm |
| **PRODUCT WEIGHT** | 0.203 kg |
| **COMPLIANCES** | CE Marked<br>RoHS conform |
| **CERTIFICATIONS** | CE |
| **GLOBAL CATALOG** | 236707 |
| **PRODUCT TYPE** | RCBO - Residual-current circuit breaker with overcurrent protection |

Powering Business Worldwide

## Product specifications

| | |
|---|---|
| **AMPERAGE RATING** | 25 A |
| **VOLTAGE RATING** | 230 V |
| **SURGE CURRENT CAPACITY** | 0.25 kA |
| **VOLTAGE TYPE** | AC |
| **WIDTH IN NUMBER OF MODULAR SPACINGS** | 2 |
| **FEATURES** | Concurrently switching N-neutral |
| **10.10 TEMPERATURE RISE** | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| **10.11 SHORT-CIRCUIT RATING** | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| **10.12 ELECTROMAGNETIC COMPATIBILITY** | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| **10.13 MECHANICAL FUNCTION** | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |
| **10.2.2 CORROSION RESISTANCE** | Meets the product standard's requirements. |
| **10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES** | Meets the product standard's requirements. |
| **10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT** | Meets the product standard's requirements. |
| **10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS** | Meets the product standard's requirements. |
| **10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION** | Meets the product standard's requirements. |
| **10.2.5 LIFTING** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.2.6 MECHANICAL** | Does not apply, since the |

## Resources

| | |
|---|---|
| DECLARATIONS OF CONFORMITY | eaton-rcd-overcurrent-protection-rcbo-declaration-eu260079en.pdf |
| ECAD MODEL | ETN.PKN6-25_1N_C_003-A-MW |
| INSTALLATION INSTRUCTIONS | eaton-mcb-rccb-rcbo-g9-il019140zu.pdf |
| MCAD MODEL | eaton-rcd-with-overcurrent-protection-3d-models-fk9051.stp |
| PEP ECO-PASSPORT | eaton-rcd-with-overcurrent-protection-pep-eato-00114-v0101-en.pdf |
| SPECIFICATIONS AND DATASHEETS | Eaton Specification Sheet - 236707 |
| WIRING DIAGRAMS | eaton-xeffect-rcbo-fl6-7-wiring-diagram.eps |

| | |
|---|---|
| **IMPACT** | entire switchgear needs to be evaluated. |
| **10.2.7 INSCRIPTIONS** | Meets the product standard's requirements. |
| **10.3 DEGREE OF PROTECTION OF ASSEMBLIES** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.4 CLEARANCES AND CREEPAGE DISTANCES** | Meets the product standard's requirements. |
| **10.5 PROTECTION AGAINST ELECTRIC SHOCK** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS** | Does not apply, since the entire switchgear needs to be evaluated. |
| **10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS** | Is the panel builder's responsibility. |
| **10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS** | Is the panel builder's responsibility. |
| **10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH** | Is the panel builder's responsibility. |
| **10.9.3 IMPULSE WITHSTAND VOLTAGE** | Is the panel builder's responsibility. |
| **10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL** | Is the panel builder's responsibility. |
| **OPERATING AMBIENT TEMPERATURE - MAX** | 40 °C |
| **OPERATING AMBIENT TEMPERATURE - MIN** | -25 °C |
| **PRODUCT RANGE** | PKN6 |
| **RATED CURRENT** | 25 A |
| **RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)** | 25 A |
| **RATED SWITCHING CAPACITY (IEC/EN 61009)** | 6 kA |
| **STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT** | 0 W |
| **TRIPPING CHARACTERISTIC** | C |
| **BUILT-IN DEPTH** | 60 mm |
| **CURRENT LIMITING CLASS** | 3 |
| **RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 60947-2)** | 0 kA |
| **AMBIENT OPERATING** | 40 °C |

| | |
|---|---|
| **TEMPERATURE - MAX** | |
| **AMBIENT OPERATING TEMPERATURE - MIN** | -25 °C |
| **FAULT CURRENT RATING** | 0.03 A |
| **HEAT DISSIPATION CAPACITY** | 0 W |
| **HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT** | 0 W |
| **NUMBER OF POLES (PROTECTED)** | 1 |
| **NUMBER OF POLES (TOTAL)** | 2 |
| **RATED OPERATIONAL VOLTAGE (UE) - MAX** | 230 V |
| **RATED SWITCHING CAPACITY** | 6 kA |
| **BASIC FUNCTION** | Combined RCD/MCB devices |
| **MOUNTING METHOD** | DIN rail |
| **EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT** | 4.8 W |
| **RATED IMPULSE WITHSTAND VOLTAGE (UIMP)** | 4 kV |
| **DEGREE OF PROTECTION** | IP20 |
| **TRIPPING** | Non-delayed |
| **OVERVOLTAGE CATEGORY** | III |
| **POLLUTION DEGREE** | 2 |
| **IMPULSE WITHSTAND CURRENT** | Partly surge-proof, 250 A |
| **LEAKAGE CURRENT TYPE** | A |
| **RELEASE CHARACTERISTIC** | C |
| **SENSITIVITY TYPE** | Type A, pulse-current sensitive |
| **FREQUENCY RATING** | 50 Hz |
| **RATED INSULATION VOLTAGE (UI)** | 440 V |
| **CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN** | 1 $mm^2$ |
| **CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX** | 25 $mm^2$ |

| | |
|---|---|
| **CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN** | 1 mm² |
| **CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX** | 25 mm² |
| **RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 61009)** | 6 kA |
| **RATED SHORT-CIRCUIT BREAKING CAPACITY (EN 61009-1)** | 6 kA |
| **NUMBER OF POLES** | Single-pole + N |
| **DISCONNECTION CHARACTERISTIC** | Undelayed |
| **TYPE** | RCBO |
| **APPLICATION** | Switchgear for residential and commercial applications |

| | |
|---|---|
| **PROJECT NAME:** | |
| **PROJECT NUMBER:** | |
| **PREPARED BY:** | |
| **DATE:** | |

**Eaton Corporation plc** Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.