




Ground Rod Clamp – LPC790



- Unique stamped body design will not crack as mechanical forces are increased
- Stainless steel threads will not strip if over-tightened
- Unique internal profile offers pull-out load in excess of four times the UL® 96 requirement
- Listed to UL® 96



Part Number	LPC790
Material	Copper
Conductor Size, UL	Class 1 - Class 2 (4/0 Max)
Ground Rod Diameter, Nominal	1/2" – 3/4"
Ground Rod Diameter, Actual (Ø)	12,7 – 17,3 mm
Height (H)	42 mm
Length (L)	44,5 mm
Width (W)	23,8 mm
Unit Weight	0,152 kg
Certifications	UL
Standard Packaging Quantity	1 pc
UPC	78285661114
EAN-13	8711893055146

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.