



Features


- A click diffuser made of acrylic thermoplastic (PMMA). Operating temperature: -20 - 70 [°C]. IK rating: 08. UV resistant. Fire hazard certificate according to IEC 60695-2-11. Compatible with the following profiles: Profile deep wide surface 30 CDE-9/T (0022590), Profile shallow wide surface 30 CDE-9/T (0022591). Transparency level 70%.

Product Overview

Product name	Cover D9 click 1m opal
Technology	Accessory
Housing	Aluminium
General application	Retail
ETIM Class	EC002557
Housing colour	Silver
Product EAN number	5410288226170
Warranty	3 years

Cover D9 click 1m opal
0022617

Technical drawings



Data table

GENERAL DATA

Product name	Cover D9 click 1m opal
Technology	Accessory
Housing	Aluminium
General application	Retail
ETIM Class	EC002557
Warranty	3 years

ELECTRICAL DATA

Control gear required	No
-----------------------	----

PHYSICAL DATA

Housing colour	Silver
Diffuser finish	Opal
Nominal Product Length (mm)	1000
Nominal Product Width (mm)	33.4

Cover D9 click 1m opal 0022617

Nominal Product Height (mm)	24.4
Weight (kg)	0.03

PACKAGING

Single packaging type	Carton
Product EAN number	5410288226170
Packaging single length / height (cm)	100.0
Packaging single width (cm)	3.0
Packaging single depth (cm)	2.0
DUN14 (outer)	05410288226170
Units per outer package	25
Packaging outer length / height (cm)	205.0
Packaging outer width (cm)	16.0
Packaging outer depth (cm)	16.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No