



Features

- Integrated LED highbay; Black aluminium housing; 13000Lm; 80 W; 163 Lm/W; 4000K; Drive current: 410mA; CRI 80; 85° beam angle; DALI dimmable; IP65; IK08; Lifespan L80:B20 92,000 hrs; (D x H) 298 x 168 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.

Product Overview

Product name	Granit IP65 DALI 13000lm 840 WB
Technology	LED
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4357105
Fixture luminous flux (lm)	13000
Luminaire efficacy (lm/W)	163
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	80
Electrical protection	Class I
Dimmable	Yes
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9017 - Traffic black
IP rating	IP65

Granit IP65 DALI 13000lm 840 WB 0039752

IK rating	IK08
Product EAN number	5410288397528
Warranty	5 years
Dimming method	DALI-2

Photometry

