



Features

- LED T5 replacement batten, seamless linking (up to 10M), ideal for direct lighting such as under cabinet or in kitchens, 120 degree beam angle, includes switch, includes 0.30m stripped cable, white polycarbonate body, includes standard and tilting brackets


Product Overview

Product name	LED PIPE L900 WW
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer, Retail
ETIM Class	EC000109
E-number FI	4278206
Fixture luminous flux (lm)	900
Luminaire efficacy (lm/W)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	9
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288513638
Warranty	3 years


LED PIPE L900 WW
0051363

Dimming method	N/A
----------------	-----

Photometry



Technical drawings



Data table

GENERAL DATA

LED PIPE L900 WW 0051363

Product name	LED PIPE L900 WW
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
E-number FI	4278206
Warranty	3 years

OPTICAL DATA

Fixture luminous flux (lm)	900
Luminaire efficacy (lm/W)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam Angle (°)	120
Photobiological Risk Group	RG0

ELECTRICAL DATA

Total power consumption (W)	9
Mains voltage (V)	220-240V
Lamp power factor	0.5
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	100
Inrush Current (A)	100
Inrush Duration (µs)	150
Glow Wire Test (°C)	650

LED PIPE L900 WW 0051363

Energy Efficiency Class (A->G) of contained light source	E
--	---

Nominal Frequency (Hz)	50/60Hz
------------------------	---------

Max. Luminaires per 10A C Breaker	146
-----------------------------------	-----

Max. Luminaires per 13A C Breaker	189
-----------------------------------	-----

Max. Luminaires per 16A C Breaker	238
-----------------------------------	-----

Max. Luminaires per 20A C Breaker	291
-----------------------------------	-----

Max. Luminaires per 10A B Breaker	85
-----------------------------------	----

Max. Luminaires per 13A B Breaker	113
-----------------------------------	-----

Max. Luminaires per 16A B Breaker	140
-----------------------------------	-----

Max. Luminaires per 20A B Breaker	175
-----------------------------------	-----

LIFETIME DATA

Lifespan L70 B50	30000
------------------	-------

PHYSICAL DATA

Housing colour	White
----------------	-------

IP rating	IP20
-----------	------

IK rating	IK03
-----------	------

Diffuser material	PC Polycarbonate
-------------------	------------------

Nominal Product Length (mm)	900
-----------------------------	-----

Nominal Product Width (mm)	24
----------------------------	----

Nominal Product Height (mm)	35
-----------------------------	----

Weight (kg)	0.13
-------------	------

PACKAGING

Single packaging type	Carton
-----------------------	--------

Product EAN number	5410288513638
--------------------	---------------

Packaging single length / height (cm)	90.4
---------------------------------------	------

Packaging single width (cm)	4.6
-----------------------------	-----

Packaging single depth (cm)	3.1
-----------------------------	-----

DUN14 (outer)	15410288513635
---------------	----------------

Units per outer package	30
-------------------------	----

Packaging outer length / height (cm)	92.0
--------------------------------------	------



LED PIPE L900 WW
0051363

Packaging outer width (cm)	25.5
Packaging outer depth (cm)	22.0

SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No